



Alloy Machined Side-Eject Tine - .472MT x 7.000L x .540OD R9990032



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

R&R Products R999F007

Specifications

| | |
|----------------------------------|---------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Machined Side-Eject |
| B - Tine Mounting Dia. | .472 in (11.9mm) |
| C - Tine Length | 7 in (178mm) |
| D - Tine Tip Outside (Hole) Dia. | .540 in (13.7mm) |
| E - Tine Tip Inside (Core) Dia. | .400 in (10.2mm) |
| F - Tine Wall Thickness | .062 in (1.6mm) |

Fits Models

Redexim Verti-Drain

GERT KAUFMANN Golf Course Management

Graf-Buttler-Strasse 7 Haimhausen, 85778
+498133907773

<https://golfkauf.rrproducts.com/>