



# Alloy Hollow Tine - .750MT x 6.500L x .660OD R108-9137



## Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

## Replaces

Toro 108-9137

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	6.5 in (165mm)
D - Tine Tip Outside (Hole) Dia.	.660 in (16.8mm)
E - Tine Tip Inside (Core) Dia.	.500 in (12.7mm)
F - Tine Wall Thickness	.058 in (1.5mm)
Savings	Volume Buy

## Fits Models

Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648  
Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880

## GERT KAUFMANN Golf Course Management

Graf-Buttler-Strasse 7 Haimhausen, 85778  
+498133907773

<https://golfkauf.rrproducts.com/>



**Alloy Hollow Tine - .750MT x 6.500L x  
.660OD  
R108-9137**



Toro ProCore 648s