



# Alloy Hollow Side-Eject Tine - .750MT x 6.500L x .570OD R108-9167



## Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

## Replaces

Toro	108-9167
------	----------

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow Side-Eject
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	6.5 in (165mm)
D - Tine Tip Outside (Hole) Dia.	.570 in (14.5mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.058 in (1.5mm)

## Fits Models

- Toro ProCore 1298
- Toro ProCore 440
- Toro ProCore 648
- Toro ProCore 660
- Toro ProCore 864
- Toro ProCore 880
- Toro ProCore 648s

**GERT KAUFMANN Golf Course Management**

Graf-Buttler-Strasse 7 Haimhausen, 85778  
+498133907773

<https://golfkauf.rrproducts.com/>