



# Alloy Machined Side-Eject Tine - .375MT x 4.000L x .350OD R100-3625



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Replaces

Toro 100-3625

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.375 in (9.5mm)
C - Tine Length	4 in (102mm)
D - Tine Tip Outside (Hole) Dia.	.350 in (8.9mm)
E - Tine Tip Inside (Core) Dia.	.236 in (6mm)
F - Tine Wall Thickness	.062 in (1.6mm)
Savings	Volume Buy

## Fits Models

Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648

## GERT KAUFMANN Golf Course Management

Graf-Buttler-Strasse 7 Haimhausen, 85778  
+498133907773

<https://golfkauf.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .375MT**  
**x 4.000L x .350OD**  
R100-3625



---

Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s