

Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .630OD







Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products R108-9174 Toro 108-9174

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Hollow Side-Eject with Carbide Tip
B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 4.75 i
Carbide Tip Carbi
D - Tine Tip Outside .630 i

(Hole) Dia.

E - Tine Tip Inside

(Core) Dia.

F - Tine Wall

Thickness

.__.

4.75 in (121mm) Carbide Tip

.630 in (16mm)

.480 in (1.22mm)

072:- (1 0----)

.072 in (1.8mm)

Fits Models

Jacobsen GA-24

GERT KAUFMANN Golf Course Management

Graf-Buttler-Strasse 7 Haimhausen, 85778 +498133907773

https://golfkauf.rrproducts.com/



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .6300D R201513



Ryan Greensaire II

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s