



# Alloy Machined Side-Eject Tine - .625MT x 4.000L x .350OD R201520



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.625 in (15.9mm)
C - Tine Length	4 in (102mm)
D - Tine Tip Outside (Hole) Dia.	.350 in (8.9mm)
E - Tine Tip Inside (Core) Dia.	.220 in (5.5mm)
F - Tine Wall Thickness	.065 in (1.7mm)

## Fits Models

Jacobsen GA-24  
Ryan GA30  
Ryan Greensaire II

## GERT KAUFMANN Golf Course Management

Graf-Buttler-Strasse 7 Haimhausen, 85778  
+498133907773

<https://golfkauf.rrproducts.com/>