



Alloy Machined Side-Eject Tine - .750MT x 4.500L x .350OD R201521



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	4.5 in (114mm)
D - Tine Tip Outside (Hole) Dia.	.350 in (8.9mm)
E - Tine Tip Inside (Core) Dia.	.250 in (6.4mm)
F - Tine Wall Thickness	.049 in (1.2mm)

Fits Models

Jacobsen GA-24
John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Ryan GA30
Ryan Greensaire II
Toro Greens Aerator
Toro ProCore 1298
Toro ProCore 440

GERT KAUFMANN Golf Course Management

Graf-Buttler-Strasse 7 Haimhausen, 85778
+498133907773

<https://golfkauf.rrproducts.com/>



Alloy Machined Side-Eject Tine - .750MT
x 4.500L x .350OD
R201521



Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s