

## Alloy Hollow Tine - .750MT x 5.500L x .520OD



R201588

## **Details**

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

## **Specifications**

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow
B - Tine Mounting	.750 in (19mm)
Dia.	
C - Tine Length	5.500 in (140mm
D. Tina Tin Outside	F20 :- (12 2)

D - Tine Tip Outside .520 in (13.2mm) (Hole) Dia.

E - Tine Tip Inside .400 in (10.2mm) (Core) Dia.

F - Tine Wall .072 in (1.8mm) Thickness

## **Fits Models**

John Deere Aercore 1000 John Deere Aercore 1500 John Deere Aercore 2000 John Deere Aercore 800 Ryan GA30

**GERT KAUFMANN Golf Course Management** 

Graf-Buttler-Strasse 7 Haimhausen, 85778 +498133907773

https://golfkauf.rrproducts.com/