

## Alloy Hollow Tine - .750MT x 5.750L x .670OD





R201652

## **Details**

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

## **Specifications**

Manufacturer R&R Products
A - Tine Type Alloy Hollow
B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 5.75 in (146mm) D - Tine Tip Outside .670 in (17mm)

(Hole) Dia.

E - Tine Tip Inside .500 in (12.7mm)

(Core) Dia.

F - Tine Wall .072 in (1.8mm)

Thickness

## **Fits Models**

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s

**GERT KAUFMANN Golf Course Management** 

Graf-Buttler-Strasse 7 Haimhausen, 85778 +498133907773

https://golfkauf.rrproducts.com/