

# Alloy Hollow Tine - .750MT x 6.500L x .570OD





R201656

## Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

#### Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow
B - Tine Mounting	.750 in (19mm)
Dia.	
C - Tine Length	6.5 in (165mm)
D - Tine Tip Outside	.515 in (13.1mm)
(Hole) Dia.	
E - Tine Tip Inside	.300 in (7.6mm)
(Core) Dia.	
F - Tine Wall	.072 in (1.8mm)
Thickness	

## **Fits Models**

Toro ProCore 1298 Toro ProCore 440 Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880 Toro ProCore 648s

# **GERT KAUFMANN Golf Course Management**

Graf-Buttler-Strasse 7 Haimhausen, 85778 +498133907773 https://golfkauf.rrproducts.com/